

vdw quality

You're not only buying a product, you're buying quality, service and reliability. Because these are our outstanding features - to your advantage.

- Tested product quality
Guaranteed application safety on your site
- Comprehensive product range - the right solution for every application case
- Our construction material consultancy service - always there when you need it
- Our application technicians will not leave you to cope with your problem alone
- 48 h delivery service - because time is money

You will find our products at leading retailers for construction materials and natural stone.

Your specialist retailer

vdw Joint filling mortar

For filling joints in natural stone, precast concrete paving, slabs and clinker stones on terraces, sidewalks, drives and roads.

- Fast and durable
- For clean paving and slab areas
- Abrasion-proof
- Frost-proof
- Eco-friendly
- no more weeds in the joints

GftK

| Product | Description | Colours | Supplied in | light traffic loads: · Garden paths · Terraces | light to medium traffic loads: · Drives · Yard areas with car traffic | medium traffic loads: · Cars and occasional truck traffic · Access roads · junctions | heavy traffic loads: · main traffic routes · Industrial roads |
|---|---|--|---|--|---|---|---|
| vdw 800 2-component Pavement joint filling mortar on epoxy resin basis Joint width from 5 mm | <ul style="list-style-type: none"> · permanently water permeable · for paving stones and slabs · frost-proof · resistant to high-pressure and brushing vacuum machines · extremely free-flowing | <ul style="list-style-type: none"> · natural · stone grey · basalt | <ul style="list-style-type: none"> · 40 kg sack · 25 kg bucket | +++ | ++ | | |
| vdw 840 N 1-component Pavement joint filling mortar on polybutadiene basis Joint width from 5 mm | <ul style="list-style-type: none"> · water permeable · ready to process · no mixing required | <ul style="list-style-type: none"> · natural · stone grey · basalt | <ul style="list-style-type: none"> · 25 kg bucket of vacuum-packed ready-mixed mortar | ++ | | | |
| vdw 850 2-component Joint mortar self-compressing on epoxy resin basis Joint width from 5 mm | <ul style="list-style-type: none"> · water permeable · can even be processed in the rain and at low temperatures · self-compressing · resistant to brush vacuum machines · frost-proof · almost no binding agent film | <ul style="list-style-type: none"> · sandcolour · stone grey · basalt | <ul style="list-style-type: none"> · 25 kg bucket | +++ | +++ | ++ | |
| vdw 870 1-component Joint strengthener Joint width from 1–5 mm | <ul style="list-style-type: none"> · water permeable · Solidification of new and existing sand joints · frost-proof · rain and brush resistant | <ul style="list-style-type: none"> · white/transparent | <ul style="list-style-type: none"> · 1 litre bottle · 5 litre canister · 10 litre canister | + | | | |

Ask about our whole range of natural and precast concrete jointing products.

Always heed our processing instructions when using our products.

(01/2006)

+++ – excellently suitable ++ – well suitable + – suitable □ – not suitable



Preparation:

Clean the surface of the object to be filled so that no residue remains.

1



Pre-wetting:

Wet the surface thoroughly.

2



Mix the pavement joint filling mortar:

Mix the contents of the sack (homogenous pre-mixed mineral materials with a binding agent component) with the contents of the binding agent bottle included in the sack in the compulsory mixer (5 minutes), in the gravity mixer (8 minutes) or using a drill with agitator attachment in the mortar bucket (5 minutes).



Add water:

Please heed the instructions on the packaging concerning the addition of water.

Filling the joints:

Spread the mortar over the complete area to be filled using a flat squeegee and work it intensively into the joints.

4



Brushing off:

Brush off excess, soil-damp mortar after approx. 15–20 minutes (at 20 °C) until the surface is completely free of residue using a stiff brush. Do not brush residue mortar into joints which are still open.

3



That's all there is to it*

6

* Application example vdw 800